

FLASH-FLUSH-FORMULA

Fluido di lavaggio pressurizzato

Già pronto all'uso con fluido di lavaggio FORMULA pressurizzato con azoto a 40 bar, FLASH-FLUSH-FORMULA permette con 4 semplici operazioni di effettuare il lavaggio dell'impianto e il conseguente flussaggio.

FLASH-FLUSH-FORMULA deve essere completato con un kit di collegamento KIT-FLASH-HVAC.

KIT-FLASH-HVAC

Il kit, che consente il semplice collegamento del FLASH-FLUSH-FORMULA alle tubazioni frigorifere, include:

- 1 tubo flessibile 900 mm mod. V/GYSS/4-4/36.
- 1 niples 1/4" SAE x 1/4" SAE.
- 1 niples 1/4" SAE x 3/8" SAE.
- 1 niples 1/4" SAE x 1/2" SAE.

Rif	Codice	Modello	Descrizione	Q.tà min.
A	13005050	FLASH-FLUSH-FORMULA	Fluido di lavaggio pressurizzato	6
B	13005043002	KIT-FLASH-HVAC	Kit collegamento HVAC	-

Rif	Codice	Dimensioni conf.	Peso conf.
A	13005050	280 x 200 x 300 mm	9,6 kg
B	13005043002	240 x 145 x 40 mm	0,4 kg



Formula

**NON CONTIENE PRODOTTI INFIAMMABILI!
NON CONTIENE PRODOTTI TOSSICI!
NON CONTIENE PRODOTTI NOCIVI!
EVENTUALI RESIDUI SONO COMPATIBILI CON I
FLUIDI ALL'INTERNO DEL SISTEMA**

CONNESSIONE SICURA? SCEGLI LA SOLUZIONE WIGAM



Collega



Stringi



Capovolgì la bomboletta



Flussa

FLASH-FLUSH-FORMULA

Pressurized flushing fluid

Ready for use flushing fluid pressurized with nitrogen at 40bar. FLASH-FLUSH/FORMULA enables to perform circuit flushing and fluxing in 4 easy operations.

FLASH-FLUSH/FORMULA must be completed with a connecting kit, KIT-FLASH-HVAC.

KIT-FLASH-HVAC

The kit, allowing the simple connection of FLASH-FLUSH-FORMULA to the circuit, includes:

- 1 flexible hose 900 mm mod. V/GYSS/4-4/36.
- 1 adapter 1/4" SAE x 1/4" SAE.
- 1 adapter 1/4" SAE x 3/8" SAE.
- 1 adapter 1/4" SAE x 1/2" SAE.

Ref	Code	Model	Description	Min. Qty
A	13005050	FLASH-FLUSH-FORMULA	Pressurized flushing fluid	6
B	13005043002	KIT-FLASH-HVAC	Connecting kit for HVAC system	-

Ref	Code	Dimensions	Weight
A	13005050	280 x 200 x 300 mm	9,6 kg
B	13005043002	240 x 145 x 40 mm	0,4 kg



Formula

DOES NOT CONTAIN FLAMMABLE PRODUCTS!
DOES NOT CONTAIN TOXIC SUBSTANCES!
DOES NOT CONTAIN HARMFUL PRODUCTS!
POSSIBLE RESIDUES ARE COMPATIBLE WITH THE FLUIDS INSIDE THE SYSTEM

SAFE CONNECTION? CHOOSE THE WIGAM SOLUTION



Connecting



Fastening



Turning upside down



Flushing and fluxing