

Magnetic lime-scale inhibitor

Antical 20.000

To be installed in the water line following the water meter. Designed for flats, houses and duplex. The use of water filters above Antical is strongly recommended. If installed next to water tanks, a minimum distance of 1 meter is required.



	Code	Connectors diameter	Flow rate lt/min	Lenght	Widht
Antical 20.000	AC201	FF 1/2"	28 at 2 bar	190 mm	88 mm
Antical 20.000	AC202	FF 3/4"	48 at 2 bar	205 mm	88 mm
Antical 20.000	AC203	FF 1"	88 at 2 bar	220 mm	88 mm

Antical 30.000/40.000



To be installed in the water line following the water meter. Designed for condominiums and industrial plants. The use of water filters above Antical is strongly recommended. If installed next to water tanks, a minimum distance of 1 meter is required.

	Code	Connectors diameter	Flow rate lt/min	Lenght	Widht
Antical 30.000 1 1/4"	AC301	FF 1/2"	28 at 2 bar	190 mm	88 mm
Antical 30.000 1 1/2"	AC302	FF 3/4"	48 at 2 bar	205 mm	88 mm
Antical 30.000 2"	AC303	FF 1"	88 at 2 bar	220 mm	88 mm
Antical 30.000 3"	AC401	FF 3"	35-38 at 3 bar	440 mm	140 mm