



ELECTROFUSION ELBOW 90°

(*) SDR min: weldable on SDR 17,6 - 17 - 13,6 - 11 - 9 - 7,4

GOMITO ELETTROSALDABILE A 90°

(*) SDR min: saldabile su SDR 17,6 - 17 - 13,6 - 11 - 9 - 7,4

PE100 SDR11 PFA/PN16 MOP5

Code Codice	ø	SDR min*	Pack. Imb.	Q.ty/Q.tà pallet	Weight Peso kg./p.	Volume m³/p.	d1	L1	t1	D	H
12EGEM020	20	17,6	30	1440	0,073	0,0006	20	50,5	34,5	32	52
12EGEM025	25	17,6	20	1920	0,100	0,0008	25	54	36,5	37	57
12EGEM032	32	17,6	15	1440	0,107	0,0006	32	57,5	36	45	65
12EGEM040	40	17,6	20	960	0,155	0,0008	40	68	42	54	74
12EGEM050	50	17,6	10	480	0,230	0,0017	50	77	47	67	85
12EGEM063	63	17,6	8	384	0,350	0,0021	63	88	53	84	100
12EGEM075	75	17,6	6	288	0,467	0,0028	75	99	58	92	111
12EGEM090	90	17,6	14	168	1,029	0,0057	90	122	67	118	132
12EGEM110	110	17,6	10	120	1,420	0,0080	110	140	79,5	139	152
12EGEM125	125	17,6	8	96	1,950	0,0100	125	152	85	158	170
12EGEM160	160	17,6	8	32	4,388	0,0270	160	200	100	197	215
12EGEM180	180	17,6	5	20	6,280	0,0432	180	213	100	220	240
12EGEM200	200	17,6	5	20	7,960	0,0432	200	250	125	240	260
12EGEM225	225	17,6	4	16	10,925	0,0540	225	266	120	280	290