



# TR/PVC

TUBO RINFORZATO IN P.V.C. (COLORE BLU) | P.V.C. REINFORCED HOSE (BLU COLOR)  
TUYAU RENFORCE EN PVC (COULEUR BLEU) | VERSTÄRKTER PVC-SCHLAUCH (BLAU)

- Tubo in gomma con rinforzo in filo di poliestere
- Confezionato in rotoli raccordati
- Pressione di lavoro 20°C = 20 bar
- Campo di temperatura -20°C / + 20°C
- Tuyau en caoutchouc avec renfort en fil de polyéther
- Emballé en rouleaux raccordés
- Pression de travail 20 °C = 20 bars
- Échelle de température -20°C / 20°C
- Rubber hose reinforced with polyester wire
- Packaged in reels with connectors
- Operating pressure 20°C = 20 bar
- Temperature range -10°C / + 60°C
- Gummischlauch mit Polyesther-Draht verstärkt
- In Rollen mit Anschlüssen verpackt
- Betriebsdruck 20°C = 20 bar
- Temperaturbereich -10°C / + 60°C



COD.	MOD.	Øest X Øint (mm)	F	L (m)	P es (bar)	P exp (bar)		
AH0379104	TR/PVC	ø 8x13	1/4F	10	20	60	1	1050
AH0379105	TR/PVC	ø 8x13	1/4F	20	20	60	1	2240
AH0379106	TR/PVC	ø 10x15	3/8F	10	20	60	1	1450
AH0379107	TR/PVC	ø 10x15	3/8F	20	20	60	1	2850
AH0379108	TR/PVC	ø 13x19	1/2F	10	20	60	1	2550
AH0379109	TR/PVC	ø 13x19	1/2F	20	20	60	1	3850